
TELESCOPIC BOOM LIFT

SPECIFICATIONS

MODELS	T18JE-2	
Measurements	Metric	Imperial
Work Height Max.	20.6m	67'7''
Platform Height Max.	18.6m	61'
Horizontal Outreach	12.74m	41'10''
Platform Length	2.44m	8'
Platform Width	0.9m	2'11''
Stowed Length	10.09m	33'1''
Overall Width	2.5m	8'2"
© Stowed Height	2.62m	8'7''
Wheelbase	2.51m	8'3''
Ground Clearance	0.37m	1'3''
PRODUCTIVITY		
Platform Capacity (unrestricted/restricted)	300/450kg	661/992 lbs
Turntable Rotation	360°	
Drive Speed-Stowed	5km/h	3.1mph
Drive Speed-Raised	0.8km/h	0.5mph
Gradeability	45%	
Max. Wind Speed	12.5m/s	28mph
Turning Radius-Inside	3.15m	10'4''
Turning Radius-Outside	6.2m	20'4''
Max. Working Slope	5°/5°	
Tires Type	Solid tires	
Tires Models	33x12-20	
POWER		
Power Source	80V 173Ah	
HYDRAULIC SYSTEM		
HYDRAULIC SYSTEM Hydraulic Oil Volume	90L	23.8gal
	90L	23.8gal



T18JE-2 Working Range 20n 18m 16m 14m 300kg 661 lbs 12m 450kg 992 lbs 10m 8m 6m 4m Ì 2m 0 0m Ō -2m ∟ -4m 4m 2m 8m 10m 12m 14m -2m 0m 6m

Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.





LINGONG HEAVY MACHINERY CO., **LTD.** Address: No. 2676, Kejia Road, Jinan, Shandong, China

Address: No. 2676, Kejia Road, Jinan, Shandong, China Email: sales@lgmg.com.cn Tel: +86 531 6787 9283