



**EFFICIENT** 





## **LGMG SCISSOR LIFT RANGE (SS SERIES)**


## **SPECIFICATIONS**

MODELS	SS0407ER-2	
Measurements	Metric	Imperial
Work Height Max.	6.5m	21'4"
Platform Height-Raised	4.5m	14'9''
Platform Length	1.29m	4'3''
Platform Width	0.7m	2'4"
Overall Length (with ladder)	1.51m	4'11''
Overall Width	0.8m	2'7''
Overall Height-Guardrails Up	2.05m	6'9"
Overall Height-Guardrails Down	1.63m	5'4"
E Extension Deck	0.6m	2'
Wheelbase	1.05m	3'5"
Ground Clearance(Stowed/Raised)	25/8mm	1''/0.3''
PRODUCTIVITY		
Max. Platform Occupants	2(in) / 0(out)	
Platform Capacity	240kg	529 lbs
Platform Capacity-Extension Deck	100kg	220 lbs
Drive Height	Full Height	
Gradeability-Lowered	25%	25%
Min. Turning Radius	1.67m	5'6"
Raise/Lower Speed	25 / 20s	
Drive Mode	Rear-wheel Drive	
Tires Type	Solid Non-marking	
Tires Size	305×100mm	12"x4"
POWER		
Power Source	24V(2x12V),95Ah,AGM	
HYDRAULIC SYSTEM		
Hydraulic Oil Volume	4L	1gal
WEIGHT		

STANDARD FEATURES	
Emergency stop button	Tubing Explosion-Proof System
Full-height drive	Charging Protection System
Alarm	Safety Arm For Troubleshooting
Flashing beacons	Standard Transport Forklift Holes
Manual brake release	Swing-out component tray
Over-tilt protection system	Automatic Braking System
Horn/Hour meter	One-Way Platform Extension Deck
Pothole guard	Intelligent diagnostic system
Telematics	

## **OPTIONAL**

AC power to platform



Please contact LGMG or a local dealer for more details.

Machine Weight

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.

2,028 lbs

920kg

