

AR14J-2 ARTICULATING BOOM LIFT





ARTICULATION BOOM LIFT

SPECIFICATIONS

MODELS	AR14J-2	(AR45J-2)	
Measurements	Metric	Imperial	
Work Height Max.	15.9m	52'2"	
Platform Height Max.	13.9m	45'7"	
Horizontal Outreach	7.7m	25'3"	
Up and Over Height	7.5m	24'7"	
Platform Length	1.83m	6'	
Platform Width	0.76m	2'6"	
Stowed Length	6.95m	22'10''	
Transport Length (jib tucked)	5.9m	19'4''	
Overall Width	2.3m	7'7''	
Stowed Height	2.24m	7'4"	
Transport Height	2.65m	8'8"	
D Wheelbase	2.25m	7'5"	
Ground Clearance	0.33m	1'1"	
PRODUCTIVITY			
Platform Capacity (unrestricted)	300kg	661 lbs	
Platform Capacity (restricted)	450kg	992 lbs	
Max. Platform Occupancy	2(unrestricted)/3(restricted)		
Turntable Rotation	355°	355°	
Drive Speed-Stowed	5km/h	3.1mph	
Drive Speed-Raised	0.8km/h	0.5mph	
Gradeability	45%	45%	
Max. Wind Speed	12.5m/s	28mph	
Turning Radius-Inside	2.9m	9'6"	
Turning Radius-Outside	5.7m	18'8"	
Max. Slope	5°/5°	5°/5°	
Tire Type	Foan	Foam-filled	
Tire Models	315/55D20		
Ground Pressure, Tyres	431.8 kPa	62.6 psi	
POWER			
Power Source	Kubota 18	Kubota 18.2kW/24.4hp	
Fuel Tank Capacity	65L	17.2gal	
HYDRAULIC SYSTEM			
Hydraulic Oil Volume	60L	15.9gal	
WEIGHT			
Machine Weight	7,400kg	16,314 lbs	

STANDARD FEATURES
Auto-leveling platform
Hydraulic rotating platform 180°
Full proportional joystick control
Descent alarm
Flashing beacons
Horn/Hour meter
Over-tilt protection system
Emergency stop button
Intelligent self-diagnosis function
Cylinder bellows
OTA remote upgrade
Dustproof components
Over-head anti-collision protection
Platform tool box
AC power to platform

OPTIONAL


Platform work light


Half-height mesh platform

Platform auxiliary guardrail

Platform pipe rack

MACHINE SIZE





Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.



