
SPECIFICATIONS

| MODELS | T34J-2 (| T115J-2) |
|--|-------------------------------|------------|
| Measurements | Metric | Imperial |
| Work Height Max. | 36.2m | 118'9'' |
| Platform Height Max. | 34.2m | 112.2" |
| Horizontal Outreach | 21.7m | 71'2'' |
| Platform Length | 2.44m | 8' |
| Platform Width | 0.9m | 2'11'' |
| Stowed Length | 13.1m | 43' |
| Length-Transport (jib tucked) | 11.3m | 37'1'' |
| Overall Width (axles retracted) | 2.4m | 7'10'' |
| • Overall Width (axles extended) | 4m | 13'1'' |
| Stowed Height | 2.74m | 9' |
| Height-Transport | 2.74m | 9' |
| B Wheelbase | 4.16m | 13'8" |
| Ground Clearance | 0.34m | 1'1'' |
| PRODUCTIVITY | | |
| Platform Capacity (unrestricted) | 300kg | 661 lbs |
| Platform Capacity (restricted) | 450kg | 992 lbs |
| Max. Platform Occupancy | 2(unrestricted)/3(restricted) | |
| Turntable Rotation | 360° | |
| Drive Speed-Stowed | 5km/h | 3.1mph |
| Drive Speed-Raised | 0.6km/h | 0.4mph |
| Gradeability | 45% | |
| Max. Wind Speed | 12.5m/s | 28mph |
| Turning Radius-Inside (axles retracted) | 6.6m | 21'8" |
| Turning Radius-Outside (axles retracted) | 9m | 29'6'' |
| Turning Radius-Inside (axles extended) | 2.6m | 8'6'' |
| Turning Radius-Outside (axles extended) | 6.2m | 20'4'' |
| Max. Working Slope | 5°/5° | |
| Tires Type | Foam-filled | |
| Tires Models | 445/50D 710 | |
| Ground Pressure, Tyres | 992.8 kPa | 144 psi |
| POWER | | |
| Power Source | Kubota 54.6kW/73.2hp | |
| Fuel Tank Capacity | 150 L | 39.6 gal |
| HYDRAULIC SYSTEM | | |
| Hydraulic Oil Volume | 220L | 58.1gal |
| WEIGHT | | |
| Machine Weight | 17,600kg | 38,801 lbs |

| STANDARD FEATURES |
|-------------------------------------|
| OTA remote upgrade |
| Intelligent self-diagnosis function |
| Auto-leveling platform |
| Hydraulic rotating platform 180° |
| Full proportional joystick control |
| Load sensitive system |
| Over-tilt protection system |
| Emergency stop button |
| Descent alarm |
| Flashing beacons |
| Horn/Hour meter |
| Dual load 300kg/450kg |
| Over-head anti-collision protection |
| Full-time active oscillating axles |
| Full-time active oscillating axles |

| OPTIONAL | |
|--------------------------------|--|
| AC power to platform | |
| Platform work light | |
| Platform anti-collision module | |
| Platform auxiliary guardrail | |
| Platform pipe rack | |

MACHINE SIZE



Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.





LINGONG HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China Email: sales@lgmg.com.cn Tel: +86 531 6787 9283