

L'un B

LEMG






LGMG TELEHANDLER


SPECIFICATIONS

MODELS	HA	HA735	
Measurements	Metric	Imperial	
Max. Lifting Height	6.9m	22'8"	
Max. Outreach	3.9m	12'10"	
Overall Length	4.91m	16'1"	
	2.41m	7'11''	
Overall Height	2.31m	7'7"	
Wheel base	2.9m	9'6"	
Wheel Track	1.95m	6'5"	
Ground Clearance	0.41m	1'4"	
PRODUCTIVITY			
Max. Capacity	3,500kg	7,716 lbs	
Gradeability-Unladen	45	45%	
Min. Turning Radius	4.1m	13'5''	
Tilt Angle	±Ę	5°	
Drive /Steering Mode	4 Wheel Drive / 4 Wheel Steer		
Primary Boom Ascending Time	9s		
Primary Boom DescendingTime	14s		
Boom Extending Time	10s		
Boom Retracting Time	9s		
Forward - First Gear Travel Speed	4.5km/h	2.8mph	
Forward - Second Gear Travel Speed	9.5km/h	5.9mph	
Forward - Third Gear Travel Speed	19km/h	11.8mph	
Forward - Fourth Gear Travel Speed	27km/h	16.8mph	
Backward - First Gear Travel Speed	4.5km/h	2.8mph	
Backward - Second Gear Travel Speed	9.5km/h	5.9mph	
Backward - Third Gear Travel Speed	19.5km/h	12.1mph	
Braking	Multiple-disk brake with oil bath on front and rear axles		
Max. Braking Distance-Unladen	≪4m	≪13'1″	
Standard Tyres	460/70 R24		
POWER			
Manufacturer	YUC	HAI	
Rated Power	73kW	97.9hp	
Max. Torque	420N.m	192.4 lb.ft	
Displacement	3,621ml	221 cu.in	
TANK CAPACITIES			
Hydraulic Oil Capacity	100L	26.4gal	
Fuel Tank Capacity	130L	34.3gal	
WEIGHT			
Machine Weight	7,300kg	16,094 lbs	





Rough terrain load chart



Please contact LGMG or a local dealer for more details. LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.

LINGONG HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China Email: sales@lgmg.com.cn Tel: +86 531 6787 9283



www.lgmglifts.com