


# SCISSOR LIFTS

## SPECIFICATIONS

MODELS	S0812-2 (S2646-2)	
Measurements	Metric	Imperial
Work Height Max.	10m	32'10"
<b>A</b> Platform Height-Raised	8m	26'3"
<b>B</b> Platform Length	2.26m	7'5"
<b>C</b> Extension Deck	0.9m	2'11"
<b>D</b> Platform Length With Extension Deck	3.16m	10'4"
<b>E</b> Platform Width	1.12m	3'8"
<b>F</b> Overall Length	2.43m	8'
<b>G</b> Overall Width	1.19m	3'11"
<b>H</b> Overall Height-Guardrails Up	2.36m	7'9"
<b>I</b> Overall Height-Guardrails Down	1.55m	5'1"
<b>J</b> Wheelbase	1.85m	6'1"
Ground Clearance(Stowed/Raised)	100/20mm	4"/ 0.8"
PRODUCTIVITY		
Max. Platform Occupants (in/out)	2 (in) / 1(out)	
Platform Capacity	450kg	992 lbs
Platform Capacity-Extension Deck	120kg	265 lbs
Drive Height	Full Height	
Gradeability-Stowed	25%	
Min. Turning Radius	2.7m	8'10"
Raise/Lower Speed	35s / 40s	
Brakes	Front-wheel Brake	
Drive Mode	4x2	
Tire Type	Solid Non-marking	
Tire Size	380x130mm	15"x5"
Ground Pressure, Tyres	1119kPa	162.3psi
POWER		
Lead-acid Battery	24V(4×6V),220Ah	
HYDRAULIC SYSTEM		
Hydraulic Oil Capacity	15L	4gal
WEIGHT		
Machine Weight	2,260kg	4,982 lbs



## STANDARD FEATURES

- Proportional controls
- Foldable guardrail
- Emergency descent
- Emergency stop button
- Tubing explosion-proof system
- Intelligent diagnostic system
- Flashing beacons
- Automatic braking system
- Over-tilt protection system
- Charging protection system
- Safety arm for troubleshooting
- Horn/Hour meter
- Standard transport forklift Holes
- Pothole guard
- Telematics
- Swing-out component tray
- Alarm
- Manual brake release

## OPTIONS

- AC power to platform
- Anti-collision protection
- Overload sensing system

Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.