
SCISSOR LIFTS

SPECIFICATIONS

MODELS	S1212-2 (S4046-2)	
Measurements	Metric	Imperial
Work Height Max.	14/9.5m (in/out)	45'11''/31'2'' (in/out)
Platform Height-Raised	12/7.5m (in/out)	39'4"/24'7" (in/out)
Platform Length	2.26m	7'5"
© Extension Deck	0.9m	2'11"
Platform Length With Extension Deck	3.16m	10'4"
Platform Width	1.12m	3'8"
Overall Length	2.43m	8'
6 Overall Width	1.19m	3'11"
Overall Height-Guardrails Up	2.63m	8'8"
Overall Height-Guardrails Down	1.8m	5'11"
• Wheelbase	1.85m	6'1"
Ground Clearance(Stowed/Raised)	100/20mm	4"/ 0.8"
PRODUCTIVITY		
Max. Platform Occupants	2 (in) / 1(out)	
Platform Capacity	320kg	705 lbs
Platform Capacity-Extension Deck	120kg	265 lbs
Drive Height	Full Height	
Gradeability-Stowed	25%	
Min. Turning Radius	2.7m	8'10''
Raise/Lower Speed	65s / 53s	
Brakes	Front-wheel Brake	
Drive Mode	4x2	
Tire Type	Solid Non-marking	
Tire Size	380x130mm	15"x5"
Ground Pressure, Tyres	1264kPa	183psi
POWER		
Lead-acid Battery	24V(4×6V),220Ah	
HYDRAULIC SYSTEM		
Hydraulic Oil Capacity	21L	5.6gal
WEIGHT		
Machine Weight	2,940kg	6,482 lbs



STANDARD FEATURES
Proportional controls
Foldable guardrail
Emergency descent
Emergency stop button
Tubing explosion-proof system
Intelligent diagnostic system
Flashing beacons
Automatic braking system
Over-tilt protection system
Charging protection system
Safety arm for troubleshooting
Horn/Hour meter
Standard transport forklift Holes
Pothole guard
Telematics
Swing-out component tray
Alarm
Manual brake release
Overload sensing system

Please contact LGMG or a local dealer for more details.

 $LGMG\ reserves\ the\ right\ to\ change\ technical\ data\ without\ prior\ notice.\ All\ photos\ and\ pictures\ in\ this\ brochure\ are\ for\ promotional\ purposes\ only.$





OPTIONS

AC power to platform

Anti-collision protection