


## **LGMG VERTICAL MAST LIFTS**


## **SPECIFICATIONS**

	1	
MODELS	M0608TE	(M1932TE)
Measurements	Metric	Imperial
Working Height Max.	7.6/6.2m in/out	24'11''/20'4'' in/out
Platform Height(Raised)	5.6/4.2m in/out	18'4"/13'9" in/out
Platform Size	0.98x0.76m	3'3"x2'6"
Overall Length	1.4m	4'7"
3 Overall Width	0.79m	2'7"
• Overall Height (Stowed)	1.99m	6'6"
• Wheelbase	1.15m	3'9"
Extension Deck	0.5m	1'8''
Ground Clearance (Stowed)	0.068m	3"
PRODUCTIVITY		
Max. Platform Occupants	1(in) / 1(out)	
Platform Capacity	200kg	441 lbs
Platform Capacity- Extension Deck	113kg	249 lbs
Drive Mode	Rear wheels drive	
Drive Speed (Stowed)	4km/h	2.5mph
Drive Speed (Rised)	0.5km/h	0.31mph
Gradeability	25%	
Tire Size	250x80mm	10''x3''
POWER		
Power Source	24V (2x12V),145Ah,AGM	
HYDRAULIC SYSTEM		
Hydraulic Oil Capacity	4.5L	1.2 gal
WEIGHT		
	4.4501	0 === !!

STANDARD FEATURES		
Proportional control	leak containment tray	
Horn/Hour meter	Emergency stop device	
Emergency descent	Intelligent diagnostic system	
Pothole guard	Charging protection system	
Tilt alarm	Overload sensing system	
Platform tool box	Solid non-marking tires	

OPTIONAL	
power to platform	Biodegradable hydraulic oil





Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.

2,535 lbs



Machine Weight